



# RAM

## DATEN ZU KRAFTSTOFFVERBRAUCH UND CO2-EMISSIONEN

Angaben zum Kraftstoffverbrauch und den CO2-Emissionen gemäß WLTP-Testzyklus.

Der tatsächliche Verbrauch und die tatsächlichen Emissionen können je nach Fahrstil von den gemessenen Werten abweichen.

Brand	Model	Fuel	Engine Type	Max Power	Max Torque	WLTP CO2 emission	WLTP Fuel consumption	Top speed	Kerb Weight	Final Gear Ratio
RAM	RAM 1500	Petrol	3.0L I6	420 Hp/313 kW/425 PS @ 5,200 rpm	636 Nm @ 3,500 rpm	311 g/km	13.1 l/100 km	173 km/h	2.438 kg	3.92
	RAM 1500	Petrol	3.0L I6	540 Hp/403 kW/547 PS @ 5,700 rpm	706 Nm @ 3,500 rpm	338 g/km	14.2 l/100 km	173 km/h	2.438 kg	3.92
	RAM 1500	Petrol	3.6L V6	305 Hp/227 kW/309 PS @ 6,400 rpm	370 Nm @ 4,800 rpm	309 g/km	13.9 l/100 km	173 km/h	2.368 kg	3.21
	RAM 1500	Petrol	5.7L V8	395 Hp/295 kW/400 PS @ 5,600 rpm	556 Nm @ 3,950 rpm	369 g/km	16.3 l/100 km	173 km/h	2.444 kg	3.92
	RAM 1500	Petrol/LPG	5.7L V8	395 Hp/295 kW/400 PS @ 5,600 rpm	556 Nm @ 3,950 rpm	343 g/km	15.2 l/100 km	173 km/h	2.539 kg	3.92
	RAM 1500 eTorque	Petrol	5.7L V8	395 Hp/295 kW/400 PS @ 5,600 rpm	556 Nm @ 3,950 rpm	362 g/km	16.0 l/100 km	173 km/h	2.481 kg	3.92
	RAM 1500 eTorque	Petrol/LPG	5.7L V8	395 Hp/295 kW/400 PS @ 5,600 rpm	556 Nm @ 3,950 rpm	337 g/km	14.9 l/100 km	173 km/h	2.576 kg	3.92
	RAM 1500 Diesel	Diesel	3.0L V6	260 Hp/194 kW/263 PS @ 5,600 rpm	651 Nm @ 1,600 rpm	296 g/km	11.3 l/100 km	171 km/h	2.534 kg	3.21
	RAM TRX	Petrol	6.2L V8	702 Hp/523kW/712 PS @4,800 rpm	882 Nm @ 4,800 rpm	422 g/km	18.6 l/100 km	160 km/h	2.815 kg	3.55
	RAM Classic	Petrol	5.7L V8	395 Hp/295 kW/400 PS @ 5,600 rpm	556 Nm @ 3,950 rpm	359 g/km	15.8 l/100 km	173 km/h	2.497 kg	3.92
	RAM Classic	Petrol/LPG	5.7L V8	395 Hp/295 kW/400 PS @ 5,600 rpm	556 Nm @ 3,950 rpm	334 g/km	14.7 l/100 km	173 km/h	2.592 kg	3.92
	Challenger SXT RWD	Petrol	3.6L V6	303 Hp/227 kW/307 PS @ 6,350 rpm	363 Nm @ 4,800 rpm	251 g/km	11.0 l/100 km	220 km/h	1.817 kg	3.07
DODGE	Challenger SXT AWD	Petrol	3.6L V6	303 Hp/227 kW/307 PS @ 6,350 rpm	363 Nm @ 4,800 rpm	271 g/km	11.8 l/100 km	220 km/h	1.912 kg	3.07
	Challenger RT	Petrol	5.7L V8	375 Hp/277 kW/380 PS @ 5,200 rpm	555 Nm @ 4,400 rpm	295 g/km	13.1 l/100 km	250 km/h	1.952 kg	3.09
	Challenger Scat Pack WB	Petrol	6.4L V8	485 Hp/362 kW/491 PS @ 6,100 rpm	644 Nm @ 4,100 rpm	322 g/km	14.2 l/100 km	270 km/h	2.026 kg	3.09
	Challenger Hellcat WB	Petrol	6.2L V8	717 Hp/535 kW/726 PS @ 6,000 rpm	889 Nm @ 4,800 rpm	315 g/km	13.9 l/100 km	315 km/h	2.080 kg	2.62
	Challenger Redeye WB	Petrol	6.2L V8	807 Hp/535 kW/808 PS @ 6,300 rpm	959 Nm @ 4,500 rpm	326 g/km	14.6 l/100 km	327 km/h	2.107 kg	2.62
	Charger Scat Pack WB	Petrol	6.4L V8	485 Hp/362 kW/491 PS @6,100 rpm	644 Nm @ 4,100 rpm	322 g/km	14.2 l/100 km	282 km/h	2.053 kg	3.09
	Charger Hellcat WB	Petrol	6.2L V8	717 Hp/535 kW/726 PS @6,000 rpm	889 Nm @ 4,800 rpm	315 g/km	13.9 l/100 km	315 km/h	2.158 kg	2.62
	Charger Redeye WB	Petrol	6.2L V8	807 Hp/535 kW/808 PS @ 6,300 rpm	959 Nm @ 4,500 rpm	326 g/km	14,6 l/100 km	315 km/h	2.157 kg	2.62
	Durango RT	Petrol	5.7L V8	360 Hp/268 kW/364 PS @5,150 rpm	529 Nm @ 4,250 rpm	325 g/km	14.5 l/100 km	233 km/h	2.518 kg	3.09
	Durango SRT	Petrol	6.4L V8	475 Hp/354 kW/481 PS @6,000 rpm	637 Nm @ 4,300 rpm	356 g/km	15.7 l/100 km	265 km/h	2.580 kg	3.70
	Durango Hellcat	Petrol	6.2L V8	710 Hp/529 kW/719 PS @6,100 rpm	874 Nm @ 4,300 rpm	365 g/km	16.1 l/100 km	290 km/h	2.604 kg	3.70

## TECHNISCHE DATEN

Die Informationen werden ohne Gewähr bereitgestellt und können technische und typografische Fehler enthalten. KW Auto behält sich das Recht vor, Daten jederzeit und ohne Verpflichtung zu ändern. Angaben zu Kraftstoffverbrauch und CO2-Emissionen werden regelmäßig aktualisiert.

2025 RAM 1500

	Tradesman	Bighorn	Rebel	Laramie	Limited	Tungsten	RHO
Body & Chassis							
Seating	6	5	5	5	5	5	5
Air Bags	6						
Powertrain							
Max. Power (kW/Hp @ rpm)	420 Hp/313 kW @ 5,200 rpm				636 Nm @ 3,500 rpm		
Max. Torque (Nm @ rpm)	540 Hp/403 kW @ 5,700 rpm				706 Nm @ 3,500 rpm		
Emission combined (CO2 g/km)*	311 g/km				338 g/km		
Fuel Consumption ( L/100 km)*	13.1 l/100 km				14.2 l/100 km		
Type	Petrol				91 Octane		
Tank capacity (L)	98				125		
Max speed (km/h)	173					165	
Engine Description	Hurricane In-line six-cylinder (I-6), Twin Turbocharged, liquid-cooled, direct injection						
Displacement	3.0L						
Factory Oil Fill	Pennzoil Ultra Platinum 0W-40 API SP MS-A0921						
Final gear ratio	3.92						
Battery	Group 94R, low-maintenance H7 730 CCA RHO: H7 AGM 80AH 800 CCA						
Weight							
Kerb weight (kg)	2.438						
Gross vehicle weight (kg)	3.500						
Gross Trailer Weight (kg)	3.500						

	All Trims	RHO
Dimensions		
Length (mm)	5.916	5.936
Width (mm)	2.084	2.235
Height (mm)	1.971	2.079
Wheelbase (mm)	3.672	3.686
Open tailgate to ground (mm)	881	983
Cargo Length at floor	1.711	1.711
Cargo width [wheelhouses]	1.687 [1.295]	1.687 [1.295]
Cargo height	543	543
Turning diameter curb-to-curb (m)	14.10	14.7
Head room space – front / rear	1.038 / 995	1.038 / 995
Leg room – foot / rear	1.040 / 903	1.040 / 903
Turning diameter curb-to-curb (m)	14.10	14.7
Ground Clearance		
Approach angle (°)	18.8	31
Departure angle (°)	20.6	25.2
Break over angle (°) [w/ skid plate]	19.4 [16.8]	21.8
Ground clearance [w/ skid plate]	222 / [209]	- / [300]

2024 RAM 1500

	Classic	Bighorn	Rebel	Laramie	Longhorn	Limited	TRX
Body & Chassis							
Seating	5/6	5/6	5	5/6	5	5	5
Assembly plant	Steerling Heights, Michigan USA						
Powertrain							
Description	HEMI V8 MDS						
Displacement	5.7 L						6.2L
Cylinders	8						
Max. Power (kW/Hp @ rpm)	295 / 395 @ 5.600						523 / 702 @6.100
Max. Torque (Nm @ rpm)	556 @ 3.950						882 @ 4.800
Final gear ratio	3.92						3.55
Max speed (km/h)	173						160
Tank capacity (L)	98 (LPG: 100)						125
Fuel							
Type	Petrol						91 Octane
Economy (combined, L/100 km)*	15.8	16.3 / eTorque 15.8 / LPG 15.2					18.6
Emission combined (CO2 g/km)*	359	369 / eTorque 362 / LPG 343					422
Weight							
Kerb weight (kg)	2.497	2.720				2.815	
Gross vehicle weight (kg)				3.500			
Gross Trailer Weight (kg)				3.500			

\* WLTP Test Cycle

	Classic	1500	1500	1500	TRX
Dimensions					
Body Cab	Crew Cab Shortbed	Quad Cab Longbed	Crew Cab Shortbed	Crew Cab Longbed	Crew Cab Shortbed
Length (mm)	5.816	5.814	5.916	6.142	5.916
Width (mm)	2.017	2.084	2.084	2.084	2.235
Height (mm)	1.970	1.973	1.971	1.971	2.055
Wheelbase (mm)	3.797	3.569	3.672	3.989	3.686
Open tailgate to ground (mm)	885	875	872	871	
Cargo Length at floor	1.712	1.937	1.711	1.937	1.711
Cargo width [wheelhouses]	1.687 [1.295]	1.687 [1.295]	1.687 [1.295]	1.687 [1.295]	1.687 [1.295]
Cargo height	509	545			543
Turning diameter curb-to-curb (m)	13,9	14.10			1.038
Gross total weight	3.500	3.500			1.040
Max towing capacity (braked)	3.500	3.500			995
Head room space - front	1.041	1.038			903
Leg room - foot	1.041	1.040			1.040
Head room space - rear	1.014	995			995
Leg room - rear	881	903			903
Turning diameter curb-to-curb (m)	14.10	14.10			14.7
Ground Clearance					
Approach angle (°)	19,8	18.9	19	18.9	30.2
Departure angle (°)	25,5	25	24.9	24.9	23.5
Break over angle (°) [w/ skid plate]	20,6	19.5 [17.5]	19.9 [17.8]	18.7 [16.7]	21.9
Ground clearance [w/ skid plate]	222	221 [208]	222 [209]	220 [207]	299.7

DODGE CHALLENGER

CHALLENGER	SXT	R/T	Scat Pack	Hellcat	Redeye
Body & Chassis					
Model code	LADH22 2EA	LADP22 28H	LADX22 24N	LADR22 26E	LADR22 27D
Assembly plant	Brampton, Ontario, Canada				
Construction	Unitized steel body, 2 Doors, 5 Seats				
Powertrain					
Description	V6 3.6L	HEMI 5.7L	HEMI 6.4L	6.2L	6.2L
Displacement	3,604	5,654	6,417	6,166	6,166
Max. Power (kW/Hp @ rpm)	227/305 @6.350	277/375 @5.150	362/485 @6.100	535/717 @6.000	602/807 @6.000
Max. Torque (Nm @ rpm)	363@4.800	555 @ 4.300	644 @4.100	889 @ 4.800	959 @ 4.800
Bore x Stroke	96 x 83	99.5 x 90.9	103.9 x 94.5	103.9 x 90.9	103.9 x 90.9
Compression ratio	10.2:1	10.5:1	10.9:1	9.5:1	9.5:1
Layout	60°	90°	90°	90°	90°
Fuel Economy (combined, L/100 km)*	11,8	13,1	14,2	13,9	14,6
Emissions combined (CO2 g/km)*	271	295	322	315	326
Max speed (km/h)	210	227	299	313	327
Max acceleration 0-100km/h (sec)	6,6	5.1	4,4	3,5	3,5
¼ mile elapsed - 400 m (sec)	14,9	13,6	12,8	11,2	11,2
@ speed (km/h)	154	170	172	208	208
Aspiration	Natural			Supercharged	
Cylinders	6	8			
Valve	24				
Type	Unleaded regular, 87 octane		Premium 91 octane		
Tank capacity (L)	70				
* WLTP Test Cycle					

Dimensions					
Length (mm)	5.026				
Width w/ mirrors (mm)	2.169				
Width w/o mirrors (mm)	1.923	1.986			
Height (mm)	1.459				
Wheelbase (mm)	2.950				
Track front	1.611	1.666			
Track rear	1.620	1.668			
Drag coefficient	0.337	0.398			
Ground clearance	130				115
Head room space fr/rr	999 / 942				
Leg room fr/rr	1.067 / 840				
Width-Shoulder room fr/rr	1.485 / 1.368				
Width-Hip room fr/rr	1.405 / 1.214				
Cargo volumes (L)	845				
Turning Diameter (m)	11.4				
Weight					
Curb weight	1.750	1.890	1.924	1.957	1.957
Weight distribution	52/48	52/48	55/45	57/43	57/43
Brakes					
Front	320 x 28	345 x 28	360 x 22	400 x 34	400 x 34
Rear	320 x 10	320 x 22	350 x 28	350 x 28	350 x 28

	SXT	R/T	Scat Pack	Helicat	Redeye
Dimensions					
Length (mm)	5.026				
Width w/ mirrors (mm)	2.169				
Width w/o mirrors (mm)	1.923	1.986			
Height (mm)	1.459				
Wheelbase (mm)	2.950				
Track front	1.611	1.666			
Track rear	1.620	1.668			
Drag coefficient	0.337	0.398			
Ground clearance	130				115
Head room space <u>fr/rr</u>	999 / 942				
Leg room <u>fr/rr</u>	1.067 / 840				
Width-Shoulder room <u>fr/rr</u>	1.485 / 1.368				
Width-Hip room <u>fr/rr</u>	1.405 / 1.214				
Cargo volumes (L)	845				
Turning Diameter (m)	11.4				
Weight					
Curb weight	1.750	1.890	1.924	1.957	1.957
Weight distribution	52/48	52/48	55/45	57/43	57/43
Brakes					
Front	320 x 28	345 x 28	360 x 22	400 x 34	400 x 34
Rear	320 x 10	320 x 22	350 x 28	350 x 28	350 x 28

## DODGE CHARGER

	Scat Pack	Hellcat	Red Eye
Body & Chassis			
Model code	LDDR48 21W/21V	LDDT48 23T	LDDT48 23Z
Assembly plant	Brampton, Ontario, Canada		
Construction	Unitized steel body		
Doors	4		
Seats	5		
Powertrain			
Description	HEMI 6.4L	6.2L	6.2L
Displacement	6,417	6,166	6,166
Max. Power (kW/Hp @ rpm)	362/485 @ 5.250	535/717 @ 6.000	602/807 @ 6.000
Max. Torque (Nm @ rpm)	644 @4.100	889 @ 4.800	959 @ 4.800
Bore x Stroke	103.9 x 94.5	103.9 x 90.9	103.9 x 90.9
Compression ratio	10.9:1	9.5:1	9.5:1
Fuel Economy (combined, L/100 km)*	14,2	13,9	14,6
Emissions combined (CO2 g/km)*	322	315	326
Layout	90°		
Cylinders	8		
Aspiration (Natural / Turbo)	Natural	Supercharged	
Valve	24		
Max speed (km/h)	280	315	N/A
Fuel			
Type	Unleaded regular, 87 Octane	Premium 91 octane	
Tank capacity (L)	70		

\* WLTP Test Cycle

	Scat Pack	Hellcat	Red Eye
Dimensions			
Length (mm)	5.100		
Width (mm)	1.905		
Height (mm)	1.510		
Wheelbase (mm)	3.052		
Track front	1.610		
Track rear	1.620		
Drag coefficient	0.335		
Head room space – front	981		
Leg room - front	1.061		
Head room space - rear	930		
Leg room - rear	1.019		
Cargo volumes (L)	467		
Weight			
Curb weight	1.920	1.991	2.057
Weight distribution	54/46	55/45	56/44
Brakes			
Front	360 x 22	400 x 34	400 x 34
Rear	350 x 28	350 x 28	350 x 28

## DODGE DURANGO

	R/T		SRT	Helicat		R/T		SRT	Helicat
Body & Chassis					Dimensions				
Model code	WDES75 22S		WDEX75 29N	WDEM75	Length (mm)	5.110			
Assembly plant	Detroit, Michigan, USA				Width (mm)	1.924			
Construction	Steel unibody				Height (mm)	1.827			
Doors	5		5	5	Wheelbase (mm)	3.042			
Seats	7 standard (2/3/2)		6 standard (2/2/2)	6 standard (2/2/2)	Track front / rear	1623 / 1627			
Powertrain					Drag coefficient	0.35			
Description	HEMI 5.7L V8		HEMI 6.4L V8	HEMI 6.2L V8	Ground clearance	207			
Displacement	5,654		6,417	6,166	Approach angle (degrees)	16.3			
Max. Power (kW/Hp @ rpm)	268/360 @ 5.150		354/475 @ 6.000	529/710 @ 6.000	Ramp break over angle (degrees)	18.1			
Max. Torque (Nm @ rpm)	529 @ 4.250		637 @4.300	889 @ 4.800	Departure angle (degrees)	21.5			
Bore x Stroke	99.5 x 90.9		103.9 x 94.5	103.9 x 90.9	1 <sup>st</sup> row	Head room: 1.013 / Leg room: 1.025			
Compression ratio	10.5:1		10.9:1	9.5:1	2 <sup>nd</sup> row	Head room: 1.011 / Leg room: 981			
Final gear ratio	3.09		3.70	3.70	3 <sup>rd</sup> row	Head room: 960 Leg room: 850			
Fuel Economy (combined, L/100 km)*	14.5		15.7	16.1	Cargo capacity (m³)	Behind 1 <sup>st</sup> row: 2.40 / 2 <sup>nd</sup> row 1.35 / 3 <sup>rd</sup> row 0.49			
Emissions combined (CO2 g/km)*	325		356	365	Weights				
Cylinders	8				Curb weight	2.677	2.717	2.717	
Aspiration (Natural / Turbo)	Natural			Supercharged	Max Vehicle Weight	3.221	3.221	3.221	
Valve	24				Payload	590	500	500	
Transfer case	Full-time AWD AWD lock 50/50	Full-time AWD Torque split: Auto 40/60	Full-time AWD Torque split: Auto 40/60	Full-time AWD Torque split: Auto 40/60	Max Towing Capacity (kg)	3.266	3.266	3.266	
	(with Opt AAN, SRT Transfer case )	Snow and tow 50/50 Sport 35/65 Track 30/70	Snow and tow 50/50 Sport 35/65 Track 30/70	Snow and tow 50/50 Sport 35/65 Track 30/70	Brakes				
Max speed (km/h)	190 (235 with opt AAN)		290	290	Front	350 x 32   380 x 34	380 x 34	400 x 36	
Max acceleration 0-100 km/h	7.1 sec		4.4 sec	3.6	Rear	330 x 22   350 x 28	350 x 28	350 x 28	
¼ mile elapsed (400 m)	15 sec		12.9 sec	12 sec	* WLTP Test Cycle				
Fuel									
Type	Unleaded, 87 octane		Premium, 91 octane	Premium, 91 octane					
Tank capacity (L)	93								